-42-

## CLAIMS

- 1. An image processing method for generating TAG information based on inclusion information which indicates an existence of significant data in code blocks for each of subbands, according to JPEG2000 standard, comprising the steps of:
- (a) accepting the inclusion information of the code blocks in a predetermined sequence in units of code blocks amounting to a number which is smaller than a number of code blocks of sub-bands in all levels; and
- (b) immediately generating and outputting TAG information corresponding to the accepted inclusion information.

15

20

10

5

- 2. The image processing method as claimed in claim 1, wherein said step (a) inputs the inclusion information of the code blocks of all level-2 and level-3 sub-bands, the inclusion information of all code blocks of a level-1 sub-band 1HL, the inclusion information of all code blocks of a level-1 sub-band 1LH, and the inclusion information of all code blocks of a level-1 sub-band 1HH, in a predetermined sequence.
- 3. The image processing method as claimed in claim 25 1, further comprising the steps of:

- (c) accepting data of numbers of zero-bit-planes in a predetermined sequence in units of code blocks amounting to a number which is smaller than a number of code blocks of subbands of all levels, said zero-bit-planes being bit-planes in which all significant bits of the code blocks in each of the sub-bands are zero; and
- (d) immediately generating and outputting ZERO-TAG information corresponding to the accepted numbers of zero-bit-planes, according to the JPEG2000 standard.

10

15

25

5

- 4. The image processing method as claimed in claim 3, wherein said step (c) inputs the data of the number of zero-bit-planes of the code blocks of all level-2 and level-3 sub-bands, the data of the number of zero-bit-planes of all code blocks of a level-1 sub-band 1HL, the data of the number of zero-bit-planes of all code blocks of a level-1 sub-band 1LH, and the data of the number of zero-bit-planes of all code blocks of a level-1 sub-band 1LH, and the data of the number of zero-bit-planes of all code blocks of a level-1 sub-band 1HH, in a predetermined sequence.
- 5. An image processing method for generating ZEROTAG information based on data of numbers of zero-bit-planes in
  which all significant bits of code blocks in each of sub-bands
  are zero, according to JPEG2000 standard, comprising the steps
  of:
  - (a) accepting data of the numbers of zero-bit-planes in

-44-

a predetermined sequence in units of code blocks amounting to a number which is smaller than a number of code blocks of subbands of all levels; and

- (b) immediately generating and outputting ZERO-TAG
  5 information corresponding to the accepted numbers of zero-bit-planes.
  - 6. The image processing method as claimed in claim 5, wherein said step (a) inputs the data of the number of zero-bit-planes of the code blocks of all level-2 and level-3 sub-bands, the data of the number of zero-bit-planes of all code blocks of a level-1 sub-band 1HL, the data of the number of zero-bit-planes of all code blocks of a level-1 sub-band 1LH, and the data of the number of zero-bit-planes of all code blocks of a level-1 sub-band 1LH, in a predetermined sequence.

10

15

20

25

7. An image processing apparatus comprising:

a TAG information analyzing circuit to generate TAG

information based on inclusion information which indicates an
existence of significant data in code blocks for each of subbands, according to JPEG2000 standard,

said TAG information analyzing circuit accepting the inclusion information of the code blocks in a predetermined sequence in units of code blocks amounting to a number which is smaller than a number of code blocks of sub-bands in all

-45-

levels, and immediately generating and outputting TAG information corresponding to the accepted inclusion information.

- 8. The image processing apparatus as claimed in claim 7, wherein said TAG information analyzing circuit inputs the inclusion information of the code blocks of all level-2 and level-3 sub-bands, the inclusion information of all code blocks of a level-1 sub-band 1HL, the inclusion information of all code blocks of a level-1 sub-band 1LH, and the inclusion information of all code blocks of a level-1 sub-band 1HH, in a predetermined sequence.
- 9. The image processing apparatus as claimed in 15 claim 7, further comprising:

20

25

a ZERO-TAG information analyzing circuit to generate ZERO-TAG information based on data of numbers of zero-bit-planes in which all significant bits of code blocks in each of sub-bands are zero, according to JPEG2000 standard,

said ZERO-TAG information analyzing circuit accepting data of numbers of zero-bit-planes in a predetermined sequence in units of code blocks amounting to a number which is smaller than a number of code blocks of sub-bands of all levels, and immediately generating and outputting ZERO-TAG information corresponding to the accepted numbers of zero-bit-planes.

-46-

10. The image processing apparatus as claimed in claim 9, wherein said ZERO-TAG information analyzing circuit inputs the data of the number of zero-bit-planes of the code blocks of all level-2 and level-3 sub-bands, the data of the number of zero-bit-planes of all code blocks of a level-1 sub-band 1HL, the data of the number of zero-bit-planes of all code blocks of a level-1 sub-band 1LH, and the data of the number of zero-bit-planes of all code blocks of a level-1 sub-band 1HH, in a predetermined sequence.

10

15

20

5

11. An image processing apparatus comprising:

a ZERO-TAG information analyzing circuit to generate

ZERO-TAG information based on data of numbers of zero-bit
planes in which all significant bits of code blocks in each of sub-bands are zero, according to JPEG2000 standard,

said ZERO-TAG information analyzing circuit accepting data of the numbers of zero-bit-planes in a predetermined sequence in units of code blocks amounting to a number which is smaller than a number of code blocks of sub-bands of all levels, and immediately generating and outputting ZERO-TAG information corresponding to the accepted numbers of zero-bit-planes.

12. The image processing apparatus as claimed in claim 11, wherein said ZERO-TAG information analyzing circuit

-47-

inputs the data of the number of zero-bit-planes of the code blocks of all level-2 and level-3 sub-bands, the data of the number of zero-bit-planes of all code blocks of a level-1 sub-band 1HL, the data of the number of zero-bit-planes of all code blocks of a level-1 sub-band 1LH, and the data of the number of zero-bit-planes of all code blocks of a level-1 sub-band 1HH, in a predetermined sequence.